



Hydraulic Bottle Jack JTxx02 Series

- Most widely used in various fields such as machinery, construction, automotive industry, etc.
- A full range of capacity from 2 to 100 ton.
- All models work both in vertical and horizontal position.
- When used in horizontal position, pump must be in the position as illustrated here.



JT0202 2 TON
JT0302 3 TON



JT0502 5 TON JT0802 8 TON JT1002 10 TON JT1202 12 TON JT1602 16 TON JT2002 20 TON JT3202 32 TON JT5002 50 TON

1KG=2.2LB 1INCH=25.4MM

Model	Lifting Capacity	Min. Height	Lifting Height	Adjust Height	Max. Height	Net Weight	Gross Weight	Measurement	Quantity Case	Quantity 1x20"
	ton	mm	mm	mm	mm	kg	kg	cm	pcs	pcs
JT0202	2	158	90	60	308	2.3	25	52x25.5x19	10	7000
JT0302	3	180	110	60	350	3.3	28	46x26.5x22.5	8	5000
JT0502	5	197	125	60	382	4.4	29	37x27.5x22.5	6	3720
JT0802	8	205	125	60	390	5.4	24	29.5x27.5x22.5	4	2400
JT1002	10	205	125	60	390	6	26	30.5x29.5x24	4	2180
JT1202	12	214	125	60	399	7.2	16	30.5x16.5x24	2	1700
JT1602	16	225	140	60	425	8.3	19	31.5x17x24.5	2	1560
JT2002	20	244	145	60	449	10.5	23	34.5x9.5x27	2	1500
JT3202	32	285	180	/	465	14.6	31	37.5x19x31	2	900
JT5002	50	285	180	/	465	22	23	23x19x31	1	480

Hydraulic Bottle Jack JTxx03 Series

- Versatile jacks can be used vertically (not upside down) or at any angle to no more than 5 degrees from vertical position.
- Machined and polished cylinder walls ensure straight lifts preventing uneven wear.
- Heat treated adjustable extension screw with cleaned lift saddle prevents slippage.
- Patented bypass mechanism protects hydraulic cylinder from overpumped durable baked blue enamel finish.



JT0203 2 TON
JT0303 3 TON



JT0503 5 TON JT0803 8 TON JT1003 10 TON JT1203 12 TON JT1503 15 TON JT2003 20 TON JT3003 30 TON JT5003 50 TON

1KG=2.2LB 1INCH=25.4MM

Model	Lifting Capacity	Min. Height	Lifting Height	Adjust Height	Max. Height	Net Weight	Gross Weight	Measurement	Quantity Case	Quantity 1x20"
	ton	mm	mm	mm	mm	kg	kg	cm	pcs	pcs
JT0203	2	158	90	60	308	2.3	25	52x25.5x19	10	6250
JT0303	3	195	125	60	380	3.3	28	46x26.5x22.5	8	4600
JT0503	5	197	125	80	402	4.4	29	37x27.5x22.5	6	3500
JT0803	8	205	125	80	410	5.4	24	29.5x27.5x22.5	4	2430
JT1003	10	205	125	80	410	6	26	30.5x29.5x24	4	2210
JT1203	12	215	125	80	420	7.2	16	30.5x16.5x24	2	1800
JT1503	15	225	140	80	445	8.3	19	31.5x17x24.5	2	1460
JT2003	20	244	145	80	469	11.5	24	34.5x19.5x27	2	1400
JT3003	30	285	180	/	465	14.6	31	37.5x19x31	2	970
JT5003	50	300	180	/	480	33	34	24x22x32	1	480

Double Ram Bottle Jack JTxx04 Series

- A wide base provides stability and strength.
- Two-stage piston design can adjust lifting height efficiently.



JT0404 4 TON JT0604 6 TON JT1204 12 TON JT2004 20 TON JT3204 32 TON JT5004 50 TON

1KG=2.2LB 1INCH=25.4MM

Model	Lifting Capacity	Min. height	Lifting Height	Adjust Height	Max. Height	Net Weight	Gross Weight	Measurement	Quantity Case	Quantity 1x20"
	ton	mm	mm	mm	mm	kg	kg	cm	pcs	pcs
JT0404	4	160	170	40	370	4.8	25.5	63x14x24	5	3300
JT0604	6	160	170	40	370	6.8	25.5	63x15x25	5	2400
JT1204	12	220	80	50	470	9.5	22	33x19x25	2	1650
JT2004	20	230	55	60	450	14.5	31	38x20x25.5	2	1100
JT3204	32	240	80	60	420	21.5	23	23x21.5x28	1	790
JT5004	50	250	80	/	420	33	34	22x20x33	1	500

Hydraulic Air Bottle Jack JTxx08 Series

- Hydraulic Cylinder with air pump.
- Carbon steel base with automatic welding makes stable quality.
- Chrome plated plunger with self-return resists corrosion and extends life.



JT0508 5 TON JT1208 12 TON JT2008A 20 TON JT2008B 20 TON JT2208 22 TON JT3008 30 TON

1KG=2.2LB 1INCH=25.4MM

Model	Lifting Capacity	Min. Height	Lifting Height	Adjust Height	Max. Height	Net Weight	Gross Weight	Measurement	Quantity Case	Quantity 1x20"
	ton	mm	mm	mm	mm	kg	kg	cm	pcs	pcs
JT0508	5	210	140	80	430	6	7	18x15x22	2300	2300
JT1208	12	250	150	80	480	12	13	24x18x27	1400	1400
JT2008A	20	260	160	80	500	17	18	28x22x28	1030	1030
JT2008B	20	210	125	60	395	15	16	28x22x23	1100	1100
JT2208	22	260	160	80	500	17	18	28x22x28	600	600
JT3008	30	280	190	/	470	25	26	30x30x29	730	730