



Floor Jack QK Series

- Features a one-piece lift arm with dual leveling mechanism and reinforced flanged side frames for added strength under load.
- Patented safety bypass system prevents over extension and accidental overloading.
- Double swivel saddle and heavy steel casters allow safe and easy positioning.



Model	Lifting Capacity	Min. Height	Lifting Height	Net Weight	Gross Weight	Quantity Case	Package	Measurement	Quantity 1x20"
	ton	mm	mm	kg	kg	pcs		cm	pcs
QKIV-1.5-B	1.5	140	155	6	7	1	Blow case	43x21x14.5	2450
QKIV-1.5-C	1.5	140	155	6	6.5	1	Color Box	41x20x13.5	2850
QKIII-1.5-B	1.5	125	175	6.5	7.5	1	Blow case	45x22.5x14.5	2200
QKIII-1.5-C	1.5	125	175	6.5	7	1	Color Box	43x20x13.5	2500
QKII-2-B	2	135	200	7.5	8.5	1	Blow case	48x23.3x15.5	1900
QKII-2-C	2	135	200	7.5	8	1	Color Box	45.5x20x14.5	2100
QKI-2-B	2	135	200	8.5	9.5	1	Blow case	48x23.5x15.5	1900
QKI-2-C	2	135	200	8.5	9	1	Color Box	45.5x21x14.5	2100

Floor Jack QKA(B) Series



Model	Lifting Capacity	Min. Height	Lifting Height	Max. Height	Net Weight	Gross Weight	Quantity Case	Package	Measurement	Quantity 1x20"
	ton	mm	mm	mm	kg	kg	pcs		cm	pcs
QKA-2-B	2	135	220	355	10.5	12	1	Blow case	53x23x15	1500
QKA-2-C	2	135	220	355	10.5	11	1	Color box	50.5x21x15	1900
QKAI-2-B	2	135	220	355	9.5	11	1	Blow case	53x23x15	1500
QKAI-2-C	2	135	220	355	9.5	10	1	Color box	50.5x21x15	1900
QKAII-2-B	2	135	250	385	12	14	1	Blow case	58.5x24x14.5	1200
QKAII-2-C	2	135	250	385	12	13	1	Color box	56x22.5x15	1350
QKB-2-B	2	130	220	350	8.2	9.3	1	Blow case	53x25x15	1400

Floor Jack FJ Series

- Features a one-piece lift arm with dual leveling mechanism and reinforced flanged side frames for added strength under load.
- Patented safety bypass system prevents over extension and accidental overloading.
- Double swivel saddle and heavy steel casters allow safe and easy positioning.



Model	Lifting Capacity	Min. Height	Lifting Height	Net Weight	Gross Weight	Quantity Case	Measurement	Quantity 1x20"
	ton	mm	mm	kg	kg	pcs	cm	pcs
FJ2 ^{1/2}	2.5	135	495	30	32	1	69x38.5x20	500
FJ2 ^{3/4}	2.75	135	495	32	34	1	69x38.5x20	500
FJ3	3	135	495	34	36	1	69x38.5x20	500
FJ3-1	3	135	495	36	38	1	73x38.5x20	500
FJ3 ^{1/2}	3.5	135	495	38	40	1	73x38.5x20	500

Floor Jack FJ-A(C/D) Series

- Welded base and cylinder to assure strength and eliminated leaks.
- Chromed pump piston and ram for added rust resistance.



Model	Lifting Capacity	Min. Height	Lifting Height	Net Weight	Gross Weight	Quantity Case	Measurement	Quantity 1x20"
	ton	mm	mm	kg	kg	pcs	cm	pcs
FJ3A	3	100	530	44	46	1	80x41x20.5	400
FJ3 ^{1/2} A	3.5	100	520	46	48	1	80x41x20.5	400
FJ3C	3	135	495	28	30	1	69x38.5x20	540
FJ3CI	3	140	430	17.5	19	1	64.5x27x16.5	890
FJ2D	2	155	800	55	59	1	125x47x21	220
FJ3D	3	140	635	58	100	1	110x47x21	220
FJ3D-1	3	140	600	80	99	1	154x46.5x28	160
FJ5D	5	160	560	90	110	1	156x42.3x32	128
FJ10D	10	170	570	135	165	1	168x52x33	95
FJ20D	20	200	580	155	170	1	166x56x40	80

